



Chamäleon GmbH
 Rudolf-Diesel-Straße, 8a
 69115 Heidelberg-Germany
 Tel.: +49-(0)-6221 520440
 Fax: +49-(0)-6221 520449
 E-mail: info@chamaeleon/produktion.de
 http://www.chamaeleon/produktion.de

TECHNICAL DATA SHEET

UNI THINNER SLOW

Article number: 13235 (1L), 13238 (5L)
Intended use: Car refinishing Product/ Thinner, Diluent

General characteristics: Effective organic solvent mix of slow evaporation for the dilution of 2K Ground coats, 2K Top coats and 2K Clearcoats. For further information concernig typical or optimum levels of use and for more precise details, please consult our Product Informations for the base products

Physical and Chemical Characteristics:

Colour shade	colourless			
Mixing ratio				
Hardener				
Thinners				
Spraying viscosity 20° C				
Application	spraying pressure	spraying nozzle	spraying operations	
Air / Flowjar – Spray gun				
Airless / Airmix				
Pot life				
Coat thickness / dry film				
Curing time / Flash off time				
Dry Object Temp. 20° C Object Temp. 60° C	recoat time	dust dry	set to touch	full hardness

Safety instructions:

Keep containers tightly closed. Keep away from heat and flame, fire heat or other potential sources of ignition. The preparation may charge electrostatically. Always use earthing leads when taking out or transferring from one container to another.

All products should be disposed of in relation to the regulations of the environmental health authorities. Protect your Environment!



Chamäleon GmbH
Rudolf-Diesel-Straße, 8a
69115 Heidelberg-Germany
Tel.: +49-(0)-6221 520440
Fax: +49-(0)-6221 520449
E-mail: info@chamaeleon/produktion.de
<http://www.chamaeleon/produktion.de>

Data: 15, March 2015

This release replaces all eventually earlier issued versions.

*For the additional information that is not included to the Technical Data Sheet apply to the supplier: e-mail: info@chamaeleon-produktion.de
See information on safety in Safety Data Sheet.*